

IN THE CLAIMS:

Claims 1, 5, 8, and 14 have been amended herein. All of the pending claims 1 through 22 are presented below. This listing of claims will replace all prior versions and listings of claims in the application. Please enter these claims as amended.

Listing of Claims:

1. (Currently Amended) A sealing method for at least one semiconductor device on a first side of a wafer substrate, the wafer substrate having the first side, a second side, and a thickness, the at least one semiconductor device having a plurality of sides and at least one bond pad thereon, said sealing method comprising:

reducing the thickness of at least a portion of the wafer substrate from the second side thereof;

coating the first side of the wafer substrate using a first removable coating having a thickness to substantially seal at least one surface of the at least one semiconductor device on the first side of the wafer substrate;

removing a portion of the wafer substrate from each of the plurality of sides of the at least one semiconductor device on the first side of the wafer substrate, the portion of the wafer substrate being removed extending from the second side of the wafer substrate to the coating on the first side of the wafer substrate;

coating the second side of the wafer substrate using a second coating to substantially seal the second side of the wafer substrate and to substantially seal the plurality of sides of the at least one semiconductor device;

removing a portion of the first removable coating on the first side of the wafer substrate for uncovering a portion of the at least one bond pad located on the at least one semiconductor device; applying a third coating to the at least one bond pad of the at least one semiconductor device, the third coating substantially sealingly engaging the at least one bond pad and substantially sealing the first removable coating; and

removing a portion of the third coating.

2. (Original) The method of claim 1, further comprising:
removing a portion of the third coating adjacent the at least one bond pad of the at least one semiconductor device.
3. (Original) The method of claim 1, further comprising:
separating the at least one semiconductor device from the wafer substrate.
4. (Original) The method of claim 1, further comprising:
separating the at least one semiconductor device from the wafer substrate by removing a portion of the second coating.
5. (Currently Amended) The method of claim 1, further comprising:
separating the at least one semiconductor device from the wafer substrate by removing a portion of the second coating and removing a portion of the first removable coating.
6. (Previously Presented) A sealing method for at least one semiconductor device on a first side of a wafer substrate, the wafer substrate having the first side, a second side, and a thickness, the at least one semiconductor device having a plurality of sides and at least one bond pad thereon, said sealing method comprising:
coating the first side of the wafer substrate with a first removable coating having a thickness to substantially seal the at least one surface of at least one semiconductor device on the first side of the wafer substrate;
reducing the thickness of at least a portion of the wafer substrate from the second side thereof by thinning the wafer substrate in at least the portion of the wafer substrate located on said at least one semiconductor device;
removing a portion of the wafer substrate from each of the plurality of sides of the at least one semiconductor device on the wafer substrate by removing a portion of the wafer substrate extending through the thickness thereof;

coating the second side of the wafer substrate with a second coating; and
etching a portion of the wafer substrate.

7. (Original) The method of claim 6, wherein the second coating comprises a resist coating.

8. (Currently Amended) The method of claim 7, wherein the removing the portion of the wafer substrate includes:
etching the wafer substrate from each side of the plurality of sides of the at least one semiconductor device on the wafer substrate, the portion of the wafer substrate removed from said each side of the plurality of sides of the at least one semiconductor device substantially extending from the second side of the wafer substrate to substantially the first removable coating on the first side of the wafer substrate through the thickness thereof.

9. (Original) The method of claim 8, further comprising:
removing the second coating of resist from the second side of the wafer substrate.

10. (Original) The method of claim 9, further comprising:
applying a third coating to the second side of the wafer substrate.

11. (Original) The method of claim 10, wherein the third coating is a coating of glass.

12. (Original) The method of claim 11, further comprising:
applying a fourth coating of resist to the first side of the wafer substrate.

13. (Original) The method of claim 12, further comprising:
etching substantially the first coating on the first side of the wafer substrate in selected areas of
the wafer substrate.

14. (Currently Amended) The method of claim 13, further comprising:
removing the fourth coating of resist on the first side of the wafer substrate after etching of the
first removable coating on the first side of the wafer substrate.

15. (Original) The method of claim 14, further comprising:
applying a fifth coating to the first side of the wafer substrate.

16. (Original) The method of claim 15, wherein the fifth coating comprises a metal
coating.

17. (Original) The method of claim 16, further comprising:
applying a sixth coating to the first side of the wafer substrate.

18. (Original) The method of claim 17, wherein the sixth coating is a resist.

19. (Previously Presented) The method of claim 18, further comprising:
etching portions of the fifth coating on the first side of the wafer substrate leaving portions of the
fifth coating remaining on the first side of the wafer substrate in predetermined areas of
the wafer substrate.

20. (Previously Presented) The method of claim 19, further comprising:
removing substantially the sixth coating from the first side of the wafer substrate uncovering
predetermined remaining portions of the fifth coating on the first side of the wafer
substrate.

21. (Original) The method of claim 20, further comprising:
dividing the wafer substrate into semiconductor devices.

22. (Original) The method of claim 21, wherein dividing the wafer substrate
comprises:
sawing the wafer substrate into semiconductor devices.

IN THE DRAWINGS:

The attached sheet of drawings includes changes to FIG. 12A. This sheet, which includes FIG. 12A, replaces the original sheet including FIG. 3.

Specifically, FIG. 12A has been revised to change the wording within the box labeled "6" to --ETCH WAFER 10 TO REMOVE PORTIONS OF WAFER 10 IN STREET AREAS 22 BETWEEN SEMICONDUCTOR CHIPS 12 UNTIL REACH GLASS LAYER 30--. No new matter has been added.